

XL Theater Kit - Specifications for XL-8 and XL-12 Models (Exceptions Noted)

Inflatable Frame Descriptions

- Commercial grade mesh reinforced PVC
- Ultra-sonic welded seams
- Inflates in under 5 minutes with included pump
- Plastic ground sheet included (.1mm clear PVC)
- Dual self-sealing air valves allow for quick deflation
- Repair kit included
- Rust-free plastic grommets for durability

Standard Screen Descriptions

- 16x9 HD Widescreen format, 4x3 format compatible
- Compatible with all types of projectors
- Hi-Definition, bright white vinyl material
- Dual-use front and rear projection capable
- Vinyl blackout screen Included (8' or 12')
- Durable, adjustable hook & loop straps for screen support
- Optional black screen lacing included
- Black Trimmed screen for a true cinema-style picture

Speaker Specifications

- Commercial grade amplified speakers
- Moisture resistant speaker cones
- Bass and treble control on speaker
- Universal speaker stand mount (stand not included)
- Line-out allows for expansion of sound system
- 2-Channel passive volume control box included
- 30 foot Stereo RCA audio cables included

Model	XL-SP-8	XL-SP-10
Woofer Size	8"	10"
Wattage	100w	120w
Frequency Response	55Hz-18kHz	50Hz-20kHz
Dimensions (in.)	18.1x12.2x10.6	21x12.2x13.5
Weight (lbs)	19.8 lbs.	37.4 lbs.
Microphone Input	YES (1/4")	YES (xlr style)
Stereo Input	YES	YES
Ground Stands Included	NO	YES

Other Accessories Included (All Models)

- (4) 6" Ground Stakes
- (4) Stabilization Rope (20') Tie-Downs
- (1) Repair Kit (4 patches and 4 tubes of glue)
- (1) Air Inflator/Deflator (UL Listed) with Hose – 120v AC
- (1) Plastic Ground Sheet
- (1) Screen and Frame Storage Duffel
- (1) Volume Control Box
- (1) set of L-R RCA Audio Cables: 30ft
- (1) set of adjustable screen straps (52 for XL-8, 70 for XL-12)

Screen Technical Specifications

- Frame Material - .6mm PVC with 1000D Substrate Mesh Reinforcement
- Screen Material – .15mm PVC
- Product Dimensions (Inflated)
 - SXL-8 – 108"x96"x60"
 - SXL-12 – 150"x120"x60"
- Product Dimensions (folded)
 - SXL-8 – 37.5"x19.5"x19.5"
 - SXL-12 – 39.5"x25.5"x25.5"
- Shipping Weights
 - SXL-8 – approx. 50lbs
 - SXL-12 – approx. 70lbs
- Air pump - 120v AC UL Listed Inflator/Deflator
 - Model 52387 (SXL-8)
 - Model 52388 (SXL-12)
- Warning tags on box and screen – Prop. 65 Compliant

Shipping May 2006

* Specifications are subject to change.